LEGEND

RAZVODNE TABLE I DISTRIBUCIJA

KWh	TRIPHASE SUPPLY P=50kW
QEN	SUPPLY PANEL "QEN"
QSS	SOUVENIR SHOP PANEL "QSS"
QUM	MECHANICAL USERS PANEL "QUM"
	DOUBLE LAYER CORRUGATED PVC SMOOTH INTERNAL PIPE. UNDERGROUND INSTALLATION ϕ=110mm PER CONTENIMENTO LINEE IMPIANTI ELETTRICI
	DOUBLE LAYER CORRUGATED PVC SMOOTH INTERNAL PIPE. UNDERGROUND INSTALLATION ϕ=63mm FOR ELECTRIC POWER LINES
	DOUBLE LAYER CORRUGATED PVC SMOOTH INTERNAL PIPE. UNDERGROUND INSTALLATION ϕ=32mm ELECTRIC AND SPECIAL POWER LINES
	LINK TO ELECTRIC PANEL
N	EARTH CONTACT

RASVJETNA TIJELA

	CAST ALUMINUM LIGHTING BODY. TEMPERED TRANSPARENT GLASS DIFFUSER EQUIPPED WITH 1 METAL HALIDE LAMPS WITH POWER 70W. DEGREE OF PROTECTION IP67. DISANO-TYPE "ASYMMETRIC1850" MODEL OR EQUIVALENT
7.5W	ALUMINIUM LIGHTING BODY IN FALSE CEILING, WITH SPOT IN WHITE ALUMINIUM. EQUIPPED WITH 3 LED P=2,5W/EACH DEGREE OF PROTECTION IP23. FOSNOVA "MILANO SMALLT"-TYPE OR EQUIVALENT.
30W	ALUMINIUM LIGHTING BODY IN FALSE CEILING, WITH SPOT IN WHITE ALUMINIUM. EQUIPPED WITH CREE LED P=30W. DEGREE OF PROTECTION IP23. FOSNOVA "MILANO 2900""-TYPE OR EQUIVALENT.
	NYLON LIGHTING BODY WITH STAINLESS STEEL FRAME, TEMPERED GLASS DIFFUSER EQUIPPED WITH LED HAVING POWER = 3.3 W. DEGREE OF PROTECTION IP67 DISANO-TYPE "MICROFLOOR LED 1634" MODEL OR EQUIVALENT
	UNBREAKABLE POLYCARBONATE BODY LIGHTING, AND POLISHED ALUMINIUM SPOT DIFFUSER WITH POLYCARBONATE. EQUIPPED WITH 2 COMPACT FLUORESCENT LAMP P=9W. DEGREE OF PROTECTION IP65. DISANO "GLOBO 1544"-TYPE OR EQUIVALENT
	LIGHTING UNBREAKABLE NYLON BODY, CAST ALUMINUM FRAME AND TEMPERED GLASS DIFFUSER. EQUIPPED WITH LED P=2,5W. DEGREE OF PROTECTION IP67 DISANO "STARLED 1623"-TYPE OR EQUIVALENT
2x58W	UNBREAKABLE SELF EXTINGUISHING POLYCARBONATE CEILING LIGHTING BODY GALVANIZED STAINLSESS STEEL SPOT AND CLEAR POLYCARBONATE DIFFUSER. EQUIPPED WITH 2 FLUORESCENT LINEAR LAMPS P=58W. DEGREE OF PROTECTION IP66. DISANO 921 HYDRO-TYPE OR EQUIVALENT
P=..W	
24W	POWERED EMERGENCY LAMP "SA"-TYPE WITH INDICATION OF THE WAY OF ESCAPE. SELF-EXTINGUISHING POLYCARBONATE BODY AND DIFFUSER, AUTONOMY 1h AND RECHARGE TIME 12h. EQUIPPED WITH COMPACT FLUORESCENT LAMP 1 P=24W/600lumen, BATTERY NiCd WITH SELF-DIAGNOSIS DEVICE. DEGREE OF PROTECTION IP65.

FC	FAN-COIL POWER POINT
RACK	RACK TP/TD
GPE	SOCKET-GROUP RUNNING ELECTRIC PLANTS FOR INSTALLATION IN WALL SECTIONS: - N°2 SOCKET 2P+N+T 10/16A P30 TYPE - N°2 SOCKET 2P+N+T 10/16A DOUBLE STEP-TYPE
	ELECTRIC BOYLER POWER POINT
	BUTTON LIGHTS ON
230V ASC	POWER POINT AND E MONOPHASE CUTTING FOR ELECTRIC DRYER
230V SCAFF	POWER POINT AND E MONOPHASE CUTTING FOR LIGHTING EXHIBITOR
230V BAR	POWER POINT AND E CUTTING BAR DESK
	CUTTING POINT MECHANICS USERS
VRV1	TRIPHASE ELECTRIC POWER POINT FOR EXETERNAL UNIT VRV N°1 SYSTEM
VRV2	TRIPHASE ELECTRIC POWER POINT FOR EXETERNAL UNIT VRV N°2 SYSTEM
SF01	MONOPHASE ELECTRIC POWER POINT CLEANER BLOWER
P.S.E.	EMERGENCY RELEASE BUTTON CONTENT WITHIN A BOX WITH GLASS TO BREAK
DIFF	SOUND SYSTEM PANEL
AIC	FIRE ALARM PANEL
AIT	BURGLAR ALARM SYSTEM PANEL
SP	INFRARED PRESENCE DETECTOR

ELEKTRO TOTEMI

TQ1	METAL TOTEM(NOT SUPPLIED) EQIPPED WITH: - GENERAL ELECTRIC PANEL "QGE" - N°2 CONTROL BUTTONS LIGHTS ON - N°1 SPEAKER FOR SOUND P=20W - N°1 CAST ALUMINUM BODY LIGHTING, ASYMMETRIC SPOT AND TEMPERATE CRYSTAL DIFFUSER, WITH 1 METAL HALIDE LAMPS P=70W. FOSNOVA "DELTA"TYPE OR EQUIVALENT. - N°1 POWERED EMERGENCY LAMP "SA"-TYPE WITH INDICATION OF THE WAY OF ESCAPE. P=24W. - N°2 SOCKETS 2P+N+T 10/16A P30-TYPE - N°2 SOCKETS 2P+N+T 10/16A DOUBLE STEP-TYPE - N°1 DATA TRANSMISSION SOCKETS RJ45 CAT.6-TYPE
TQ2	METAL TOTEM(NOT SUPPLIED) EQIPPED WITH: - POLIVALENT HALL ELECTRIC PANEL "QSP" - N°2 CONTROL BUTTONS LIGHTS ON - N°1 SPEAKER FOR SOUND P=20W - N°1 CAST ALUMINUM BODY LIGHTING, ASYMMETRIC SPOT AND TEMPERATE CRYSTAL DIFFUSER, WITH 1 METAL HALIDE LAMPS P=70W. FOSNOVA "DELTA"TYPE OR EQUIVALENT. - N°1 POWERED EMERGENCY LAMP "SA"-TYPE WITH INDICATION OF THE WAY OF ESCAPE. P=24W. - N°2 SOCKETS 2P+N+T 10/16A P30-TYPE - N°2 SOCKETS 2P+N+T 10/16A DOUBLE STEP-TYPE - N°1 DATA TRANSMISSION SOCKETS RJ45 CAT.6-TYPE
TQ3	METAL TOTEM(NOT SUPPLIED) EQIPPED WITH: - QUADRO ELETTRICO WINE BOUTIQUE "QWB" - N°4 CONTROL BUTTONS LIGHTS ON - N°1 SPEAKER FOR SOUND P=20W - N°1 CAST ALUMINUM BODY LIGHTING, ASYMMETRIC SPOT AND TEMPERATE CRYSTAL DIFFUSER, WITH 1 METAL HALIDE LAMPS P=70W. FOSNOVA "DELTA"TYPE OR EQUIVALENT. - N°1 POWERED EMERGENCY LAMP "SA"-TYPE WITH INDICATION OF THE WAY OF ESCAPE. P=24W. - N°2 SOCKETS 2P+N+T 10/16A P30-TYPE - N°2 SOCKETS 2P+N+T 10/16A DOUBLE STEP-TYPE - N°1 DATA TRANSMISSION SOCKETS RJ45 CAT.6-TYPE
TM	METAL TOTEM(NOT SUPPLIED) EQIPPED WITH: - TOUCH SCREEN (Arrangement) - N°1 INTERFACE DEVICE (GATEWAY) FIRE PLANT - N°2 CONTROL BUTTONS LIGHTS ON - N°1 SPEAKER FOR SOUND P=20W - N°1 CAST ALUMINUM BODY LIGHTING, ASYMMETRIC SPOT AND TEMPERATE CRYSTAL DIFFUSER, WITH 1 METAL HALIDE LAMPS P=70W. FOSNOVA "DELTA"TYPE OR EQUIVALENT. - N°1 POWERED EMERGENCY LAMP "SA"-TYPE WITH INDICATION OF THE WAY OF ESCAPE. P=24W. - N°1 INFRARED DETECTOR BURGLAR ALARM SYSTEM. - N°2 SOCKETS 2P+N+T 10/16A P30-TYPE - N°2 SOCKETS 2P+N+T 10/16A DOUBLE STEP-TYPE - N°1 DATA TRANSMISSION SOCKETS RJ45 CAT.6-TYPE - N°1 SOCKETS TV/SAT
T1	METAL TOTEM(NOT SUPPLIED) EQIPPED WITH: - N°2 CONTROL BUTTONS LIGHTS ON - N°1 SPEAKER FOR SOUND P=20W - N°1 CAST ALUMINUM BODY LIGHTING, ASYMMETRIC SPOT AND TEMPERATE CRYSTAL DIFFUSER, WITH 1 METAL HALIDE LAMPS P=70W. FOSNOVA "DELTA"TYPE OR EQUIVALENT. - N°1 POWERED EMERGENCY LAMP "SA"-TYPE WITH INDICATION OF THE WAY OF ESCAPE. P=24W. - N°1 INFRARED DETECTOR BURGLAR ALARM SYSTEM. - N°2 SOCKETS 2P+N+T 10/16A P30-TYPE - N°2 SOCKETS 2P+N+T 10/16A DOUBLE STEP-TYPE - N°1 DATA TRANSMISSION SOCKETS RJ45 CAT.6-TYPE
T2	METAL TOTEM(NOT SUPPLIED) EQIPPED WITH: - N°2 CONTROL BUTTONS LIGHTS ON - N°1 SPEAKER FOR SOUND P=20W - N°1 CAST ALUMINUM BODY LIGHTING, ASYMMETRIC SPOT AND TEMPERATE CRYSTAL DIFFUSER, WITH 1 METAL HALIDE LAMPS P=70W. FOSNOVA "DELTA"TYPE OR EQUIVALENT. - N°1 BODY LIGHTING WITH EMERGENCY FUNCTION. - N°2 SOCKETS 2P+N+T 10/16A P30-TYPE - N°2 SOCKETS 2P+N+T 10/16A DOUBLE STEP-TYPE - N°1 DATA TRANSMISSION SOCKETS RJ45 CAT.6-TYPE
T3	METAL TOTEM(NOT SUPPLIED) EQIPPED WITH: - N°3 CONTROL BUTTONS LIGHTS ON - N°1 SPEAKER FOR SOUND P=20W - N°1 CAST ALUMINUM BODY LIGHTING, ASYMMETRIC SPOT AND TEMPERATE CRYSTAL DIFFUSER, WITH 1 METAL HALIDE LAMPS P=70W. FOSNOVA "DELTA"TYPE OR EQUIVALENT. - N°1 POWERED EMERGENCY LAMP "SA"-TYPE WITH INDICATION OF THE WAY OF ESCAPE. P=24W. - N°2 SOCKETS 2P+N+T 10/16A P30-TYPE - N°2 SOCKETS 2P+N+T 10/16A DOUBLE STEP-TYPE - N°1 DATA TRANSMISSION SOCKETS RJ45 CAT.6-TYPE
TR	RETRACTABLE MINI-TOWER - N°2 SOCKETS 2P+N+T 10/16A P30-TYPE - N°3 SOCKETS 2P+N+T 10/16A DOUBLE STEP-TYPE - N°2 DATA SOCKETS RJ45 CAT.6-TYPE
	list: 01