WINDOWS ABACUS

External	OUTLINE OF FURNITURE	pos 1

development scheme

development scheme

designation sheme	144/267 (1)
mason measures	144cm x 267cm

description

INSTALLATION OF FIRST CLASS OAK SEASONED DOUBLE DOOR, UNDER THE SCHEME OF THE PROJECT 3 KEYS BRASS CYLINDER LOCK AND 3 PILLARS FOR EACH DOOR. FINAL PROTECTION WITH TRANSPARENT FLATTING.

NOTE: all measures must be verified on site

	TOTAL
GROUND FLOOR	1
Σ	1

External	OUTLINE OF FURNITURE	pos 2

development scheme

development scheme

designation sheme	101/267 (2)
mason measures	101cm x 267cm

description

INSTALLATION OF FIRST CLASS OAK SEASONED DOUBLE DOOR, UNDER THE SCHEME OF THE PROJECT 3 KEYS BRASS CYLINDER LOCK AND 3 PILLARS FOR EACH DOOR. FINAL PROTECTION WITH TRANSPARENT FLATTING.

NOTE: all measures must be verified on site

	TOTAL
GROUND FLOOR	1
Σ	1

External	OUTLINE OF FURNITURE	pos 3

development scheme

development scheme

designation sheme	92/153 (3)
mason measures	92cm x 153cm

description

INSTALLATION OF DOUBLE PINE FIR WINDOW.ALUMINIUM ANODIZED IRONMONGERY, CHOSEN BY DESIGNER. RUBBER SEALS. INSTALLING A DRIP ON THE BOTTOM FOR THE FLOW OF RAIN WATER. INSULATING GLASS 4+12+4 mm THICK. THE WINDOWS MUST HAVE THE SHELTER. WINDOWS AND SHELTERS SHALL BE PROTECTED WITH TRANSPARENT FLATTING.

NOTE: all measures must be verified on site

	TOTAL
GROUND FLOOR	3
Σ	3

External	OUTLINE OF FURNITURE	pos 4

development scheme

development scheme

designation sheme	90/153 (4)
mason measures	90cm x 153cm

description

INSTALLATION OF DOUBLE PINE FIR WINDOW.ALUMINIUM ANODIZED IRONMONGERY, CHOSEN BY DESIGNER. RUBBER SEALS. INSTALLING A DRIP ON THE BOTTOM FOR THE FLOW OF RAIN WATER. INSULATING GLASS 4+12+4 mm THICK. THE WINDOWS MUST HAVE THE SHELTER. WINDOWS AND SHELTERS SHALL BE PROTECTED WITH TRANSPARENT FLATTING.

NOTE: all measures must be verified on site

	TOTAL
GROUND FLOOR	3
Σ	3

External	OUTLINE OF FURNITURE	pos 5

development scheme

development scheme

designation scheme	100 / 270 (5)
measures	100cm x 270cm

description

INSTALLATION OF FIRST CLASS OAK SEASONED DOUBLE DOOR, UNDER THE SCHEME OF THE PROJECT 3 KEYS BRASS CYLINDER LOCK AND 3 PILLARS FOR EACH DOOR. FINAL PROTECTION WITH TRANSPARENT FLATTING.

NOTE: all measures must be verified on site

	TOTAL
GROUND FLOOR	1
Σ	1